



[\[APPLY CONFIGURATION\]](#) [\[REBOOT\]](#)

System Information

Settings

[General Settings](#)

[IP Settings](#)

[Wireless Settings](#)

Services

[QOS Settings](#)

[Firewall Settings](#)

[DHCP Settings](#)

[Port Forwarding](#)

Security

[Wireless](#)

[Device Settings](#)

Status

[Interfaces](#)

[Services](#)

Commands

[Firmware Upgrade](#)

[Load Configuration](#)

[Save Configuration](#)

Wireless Settings

Fragmentation Threshold:	<input type="text" value="2346"/>	(256-2346)
RTS/CTS Threshold:	<input type="text" value="2347"/>	(0-2347)
Beacon Interval:	<input type="text" value="100"/>	(20-1024 milliseconds)
DTIM:	<input type="text" value="2"/>	(1-10)
ACK Timeout:	<input type="text" value="15"/>	(5-60)
WLAN Association Timeout:	<input type="text" value="600"/>	(60-6000)
WLAN Mode:	<input type="text" value="802.11b/g"/>	
Data Rate:	<input type="text" value="Auto"/>	
Authorization Algorithm:	<input type="text" value="Open System"/>	
Preamble Type:	<input type="text" value="Long"/>	
Broadcast ESSID:	<input type="text" value="Enabled"/>	
Intra BSS Traffic:	<input type="text" value="Enabled"/>	
CCA Mode:	<input type="text" value="2"/>	
WDS1:	<input type="text" value="00:00:00:00:00:00"/>	
WDS2:	<input type="text" value="00:00:00:00:00:00"/>	
WDS3:	<input type="text" value="00:00:00:00:00:00"/>	
WDS4:	<input type="text" value="00:00:00:00:00:00"/>	
WDS5:	<input type="text" value="00:00:00:00:00:00"/>	
WDS6:	<input type="text" value="00:00:00:00:00:00"/>	
WDS7:	<input type="text" value="00:00:00:00:00:00"/>	
WDS8:	<input type="text" value="00:00:00:00:00:00"/>	
Wireless Traffic Forwarding:	<input type="text" value="Disabled"/> to MAC address:	<input type="text" value="00:00:00:00:00:00"/>